



1. USE CURRENT EDITION OF THE AASHTO A POLICY ON GEOMETRIC DESIGN OF HIGHWAYS AND STREETS FOR DESIGN OF ROADWAY ELEMENTS
2. USE CURRENT EDITION OF THE AASHTO ROADSIDE DESIGN GUIDE FOR CLEAR ZONE REQUIREMENTS
3. PROVIDE A 60 INCH x 60 INCH PASSING AREA ON SIDEWALKS OF LESS THAN 60 INCH WHEN THERE IS NOT A HARD SURFACE PASSING AREA OF 60 INCH MINIMUM WIDTH IN A 200 FOOT SEGMENT

<p align="center">UTAH DEPARTMENT OF TRANSPORTATION</p> <p align="center">STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION</p> <p align="center">SALT LAKE CITY, UTAH</p>		<p align="center">AUG.28,2003</p>
<p align="center">RECOMMENDED FOR APPROVAL</p>		<p align="center">DATE</p>
<p align="center">CHAIRMAN STANDARDS COMMITTEE</p>		<p align="center">AUG.28,2003</p>
<p align="center">APPROVED</p>		<p align="center">DATE</p>
<p align="center">DEPUTY DIRECTOR</p>		

UTAH DEPARTMENT OF TRANSPORTATION
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION

SIDEWALKS AND SHOULDERS ON URBAN ROADWAYS

STD DWG
GW 11

STANDARD DRAWING TITLE